

Division Energy

Topics and competencies at a glance:

Benefit from more than 20 years experience in fuel processor development for stationary, mobile (aviation, maritime, ground transport) and portable applications. Apart from the reformer, the fuel cell hydrogen supply requires devices for evaporation, heat exchangers, and in case of low temperature PEM fuel cell technology a reactor for complete CO removal and balance-of-plant. The whole assembly is named fuel processor. IMM has developed compact and highly integrated high-performance components for that. The fuel processor design needs to be optimized for your specific application:

- the fuel cell type
- the power range
- the specific environment
- the specific market requirements (achievable price and sales numbers) because fabrication techniques need to be chosen accordingly

Talk to our experts to get the optimum solution for your system!

Contact

Dr. Gunther Kolb
Head of Division Energy
Phone: +49 6131 990-341
gunther.kolb@imm.fraunhofer.de

Fraunhofer Institute for Microengineering and Microsystems IMM
Carl-Zeiss-Strasse 18-20
55129 Mainz
Germany
www.imm.fraunhofer.de

All flyers of the division ENERGY
<https://s.fhg.de/flyers-energy>

© Fraunhofer IMM, Mainz 2023



Hydrogen supply for mobility

IMM compact diesel
reformer

Fossil diesel can be processed now, synthetic diesel is available already nowadays (SHELL VPower), diesel can be produced from renewable sources in future, also from carbon dioxide from industrial processes such as cement fabrication or even from the atmosphere. The conversion of diesel to hydrogen (named reforming) is easier compared to gasoline, which requires higher temperature of the reforming process. The reformat is then fed to a fuel cell (possible are high and low temperature PEM fuel cells, but also solid oxide fuel cells) which produce electric power.

Catalytic autothermal diesel reforming


IMM has developed a highly compact autothermal diesel reformer and fuel processor components:

- catalyst coating similar to automotive exhaust cleaning reduces catalyst demand further
- stable catalyst operation at partial load allows system modulation
- reactor fabrication similar to automotive exhaust gas treating systems (core part are monoliths, several suppliers world-wide available)
- catalyst technology is suitable for fossil and synthetic diesel, this allows a seamless transition of fossil diesel based power generation towards future sustainability
- compact water-gas shift reactor with integrated air cooling for CO clean-up (especially required for PEM fuel cells)
- compact preferential oxidation reactor with integrated evaporation cooling for CO fine-clean-up (especially required for low temperature PEM fuel cells)

IMM diesel autothermal reforming catalyst technology – tailor-made for the fuel

Our excessive experience in diesel reforming and related catalyst development proved that steam reforming is not suited for conversion of diesel fuels. Rather autothermal reforming has to be applied.

Microtechnology enables the development of compact and efficient systems.«



- Autothermal diesel reforming is operated in the temperature range between 750 – 800 °C thermally self-sustaining through addition of steam and air to the diesel feed.
- Therefore related catalysts are not sensitive to air exposure.
- Thermodynamic equilibrium dictates the generation of significant amounts of carbon monoxide in the reformer.
- IMM has self-developed, highly active, robust water-gas shift catalyst technology available for the first stage of carbon monoxide removal and robust preferential oxidation catalyst technology for the second stage (fine clean-up down to below 10 ppm carbon monoxide).

IMM compact autothermal diesel reformer reactor technology – tailor-made for the reaction

Diesel autothermal reformer reactors are monolithic reactors, which have been developed for automotive applications.

- They do not suffer from catalyst attrition – especially important for mobile applications.
- The catalyst applied as coating is fully accessible and consequently the required catalyst mass is minimized.
- The reaction is self-sustaining through air addition (partial oxidation generates heat which is partially consumed by steam reforming downstream in the reactor).

The robustness of this technology has been proven in practical applications under conditions of start-up, stationary operation and load changes.